

**DECK DESIGN**: A Site Design Form with drawing must be submitted to the office for approval before you build.


Deliveries: Clients must be on-site to receive all deliveries.

- No construction or deliveries allowed on Long Weekends in July and August.
- Upon exiting, Decks must be removed or sold to the Resort, decks cannot be sold to other campers.
- Allowed:
  - New wood: pressure treated, cedar or composite
  - Staining of deck in neutral colours
  - Stairs from the top of the deck to the door of the trailer
  - o 10x10 sections bolted together to the length of the trailer
  - All decks sit on the ground and are free-floating
  - O All deck frames must rest upon patio stones.
- Not Allowed:
  - No decking under gooseneck of 5<sup>th</sup> wheels
  - No used wood, pallets or skids
  - Decks cannot be connected to trailer
  - No painting of decks (because it chips).
  - No: Railings, privacy fencing, lean-to's and lattice
  - No elevated decks
  - No fridges or other large appliances on decks
  - O No Concrete blocks, Sonol Tube or deck blocks.

## **DECK CONSTRUCTION**

- Multiple 10x10 sections bolted together
- Maximum depth: 10ft deep
- Maximum length: the total length of the trailer (excluding tongue and gooseneck).
  - e.g. 28 ft trailer = 10x10 + 10x10 + 10x8. All sections must be bolted together. (diagram available at office)
- Maximum height: 10 inches to the top board
- All deck frames must rest upon patio stones. Not allowed: Concrete, Sonol Tube or deck blocks.
- Joists: 2' x 4' or 2' x 6'; Joists should be 12 or 16 inches on center
- Top boards: 5/4"x6 or 2x6
- One inch overhang of top boards is suggested so make your frame 2 inches shorter on the length and width.

## Blue Sky Rv Resort Deck Design



## Two Sections:

- 26 2x6x10 Joists Pressure treated
- 44 5/4x6x10 Top deck boards pressure treated
- 6 6x6x1 patio stones
- 2 Box of 3 inch Deck screws
- 6 1/2 x 5 Inch carriage bolts with washers and nuts